

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3206A

SIMOTICS SD - 200 L - IM B3 - 2p

| | | |
|------------------|-----------------|-----------|
| Client order no. | Item-No. | Offer no. |
| Order no. | Consignment no. | Project |
| Remarks | | |

Electrical data

Safe Area

| U [V] | Δ / Y | f [Hz] | P [kW] | P [hp] | I [A] | n [1/min] | M [Nm] | $\eta^{3)}$ | | | $\cos\phi^{3)}$ | | | I_A/I_N I_f/I_N | M_A/M_N T_f/T_N | M_K/M_N T_B/T_N | IE-CL |
|-----------------------------------------|--------------|-----------|-----------|-----------|----------|--------------|-----------|--------------|------|------|------------------------|------|------|------------------------|------------------------|------------------------|-------|
| | | | | | | | | 4/4 | 3/4 | 2/4 | 4/4 | 3/4 | 2/4 | | | | |
| DOL duty (S1) - 155(F) to 130(B) | | | | | | | | | | | | | | | | | |
| 400 | Δ | 50 | 45.00 | -/- | 79.00 | 2950 | 146.0 | 94.0 | 94.5 | 93.9 | 0.87 | 0.84 | 0.76 | 7.1 | 2.5 | 3.2 | IE3 |
| 690 | Y | 50 | 45.00 | -/- | 46.00 | 2950 | 146.0 | 94.0 | 94.5 | 93.9 | 0.87 | 0.84 | 0.76 | 7.1 | 2.5 | 3.2 | IE3 |
| 460 | Δ | 60 | 51.00 | -/- | 78.00 | 3555 | 137.0 | 93.6 | 93.8 | 93.2 | 0.88 | 0.85 | 0.78 | 7.4 | 2.6 | 3.2 | IE3 |
| 460 | Δ | 60 | 45.00 | -/- | 70.00 | 3560 | 121.0 | 93.6 | 93.3 | 92.3 | 0.86 | 0.82 | 0.74 | 8.4 | 3.0 | 3.7 | IE3 |
| IM B3 / IM 1001 | | FS 200 L | | IP55 | | UKCA | | IEC/EN 60034 | | | IEC, DIN, ISO, VDE, EN | | | | | | |

Environmental conditions : -20 °C - +40 °C / 1000 m

Locked rotor time (hot / cold) : 22.7 s | 44.6 s

Mechanical data

| | | | | |
|----------------------------------------------------------------------------|--------------------------------|--------------------------------|---------------------------------|----------------------------------------------------|
| Sound level (SPL / SWL) at 50Hz 60Hz | 72 / 85 dB(A) ^{2) 3)} | 78 / 91 dB(A) ^{2) 3)} | Vibration severity grade | A |
| Moment of inertia | 0.1700 kg m ² | | Thermal class | F |
| Bearing DE NDE | 6212 2Z C3 | 6212 2Z C3 | Duty type | S1 |
| bearing lifetime | | | Direction of rotation | bidirectional |
| L_{10mh} , F_{Rad} min 50 60Hz ¹⁾ for coupling operation | 40000 h | 32000 h | Frame material | cast iron |
| Regreasing device | Without | | Net weight of the motor (IM B3) | 245 kg |
| Grease nipple | -/- | | Coating (paint finish) | Standard paint finish C2 |
| Type of bearing | Locating bearing NDE | | Color, paint shade | RAL7030 |
| Condensate drainage holes | With (standard) | | Motor protection | (B) 3 PTC thermistors - for tripping (2 terminals) |
| External earthing terminal | With (standard) | | Method of cooling | IC411 - self ventilated, surface cooled |

Terminal box

| | | | |
|--------------------------|-----------|--------------------------------|---------------------|
| Terminal box position | top | Max. cross-sectional area | 25 mm ² |
| Material of terminal box | cast iron | Cable diameter from ... to ... | 27 mm - 35 mm |
| Type of terminal box | TB1 L01 | Cable entry | 2xM50x1,5-2xM20x1,5 |
| Contact screw thread | M6 | Cable gland | 4 plugs |

Notes:

I_A/I_N = locked rotor current / current nominal
 M_K/M_N = locked rotor torque / torque nominal
 M_f/M_N = break down torque / nominal torque
 1) L10mh according to DIN ISO 281 10/2010
 2) at rated power / at full load
 3) Value is valid only for DOL operation with motor design IC411

| | | | | | | |
|-------------------------------|-----------------------------|-------------------------------|-----------------------------|---------------------------------------------------------------------------------------------------------------------|--------------------------------|----------------|
| responsible dep. DI MC LVM | technical reference | created by DT Configurator | approved by | <i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i> | Link documents | |
| | document type datasheet | document status released | | | document number | |
| | title 1LE1503-2AA63-4AB4 | rev. 943 | creation date 2023-06-20 | | | language en |
| © Siemens AG 2023 | | | | | | |

