



	X	Y	Z
POINT A	230.85	-201.74	0
POINT B	230.85	0	0
POINT C	230.85	202.11	0
POINT D	230.85	201.15	162.91
POINT E	230.85	0.36	162.91
POINT F	230.85	200.79	162.91

NOTES	ITEM	PART NO.	DESCRIPTION	MEMBER	QTY
	2		DESKA		2
	1		DEFORMATION MEMBER		6

**WARNING**  
 THE USER SHALL BE RESPONSIBLE FOR THE PROPER USE OF THIS PRODUCT. THIS DRAWING IS SUBJECT TO U.S. EXPORT ADMINISTRATION REGULATIONS AND INTERNATIONAL TRADE RESTRICTIONS OR REGULATIONS.

**COPYRIGHT**  
 ORIGINALLY CREATED AND REVISED IN THE YEARS AS IDENTIFIED IN THE RELEASING ECR. BOBCAT COMPANY RESERVES ALL RIGHTS.

**PROPRIETARY NOTICE**  
 THIS DOCUMENT CONTAINS CONFIDENTIAL AND TRADE SECRET INFORMATION. IT IS THE PROPERTY OF BOBCAT COMPANY AND IS GIVEN TO THE RECEIVER IN CONFIDENCE AND AGREES THAT THE RECEIVER WILL NOT USE THE DOCUMENT OR ANY INFORMATION THEREIN TO REPRODUCE, DISSEMINATE, OR IN ANY MANNER DISCLOSE THE DOCUMENT OR THE CONFIDENTIAL OR TRADE SECRET INFORMATION THEREIN; AND (4) UPON COMPLETION OF DEMAND, RETURN THE DOCUMENT AND ALL COPIES THEREOF.

**TOLERANCES:**  
 UNLESS OTHERWISE SPECIFIED  
 SEE BOBCAT STANDARD DE-L-FOR  
 SHEETMETAL BEND RADIUS TOLERANCE  
 X [X.X] ± 0.1 [1]  
 X.X [X.XX] ± 0.0 [04]  
 X.XX [X.XXX] ± .25 [010]

**WELD SYMBOLS PER ANSI/ASME A2.4**

**THIRD ANGLE PROJECTION**  
 (CHARACTERS OR <TEXT> PER BCI STD PR44)

**ECN**  
 MATL.  
 TREAT.  
 HARD.

**S&A** 1787.19 in<sup>2</sup> 11530.26 cm<sup>2</sup>  
**WT** 209.45 lb 95.00 kg

**ANGULAR ± 1°**  
**FILLETS & RADII ± 1.5 [6]**

**Bobcat Company**  
 WEST FARGO, NORTH DAKOTA, USA

**TITLE** HEXAPOD ASSEMBLY  
**DWG. NO.** HEXAPOD  
**SHT 1/1**

REV	DESCRIPTION	CHG	NOTICE	DWN	SHEET
0					