


- FR**
- WASHED RIVER GRAVEL FRACTION $\frac{16}{32}$ Tl.50 mm
 - FILTEK 300 Tl.3 mm
 - Elastek 40 (50) special Dekor Tl.4 (5) mm
 - XPS Styrodur® 3000 S Tl.200mm
 - EPS 200 Incline sloping layer After 1000 mm Tl.150 - 275 mm
 - PARABIT AL + V S35 vapor barrier
 - Dekprimer asphalt penetration coating Tl.3.5mm
DEKPRIMER is cold processable bituminous emulsion primer on concrete, .
 - RC monolithic reinforced concrete slab. Tl.200mm
C40/50

±0,000 = 192,64 m ASL

DEVELOPED BY: Bc.M. Faeyz Yosufi		CONSULTED & CONTROLLED: doc. Ing. František Kulhánek CSc.		Fakulta stavební ČVUT 	
DREW BY: Bc.M. Faeyz Yosufi		CUSTOMER: Faculty of Civil Engineering ČVUT / CTU			
General Purpose: Multifunctional building				PARE:	
Attachment name: D02 Roof drainage pipes				Format:	2XA4
				Date:	13.10.2019
				Purpose	building permit
				Archive Issues	----
				Scale. 1:10	Drawing No. D2