

SIMATIC ET 200SP, Analog input module, AI Energy Meter 480V AC ST, suitable for BU type D0, channel diagnostics



| General information | |
|---|----------------------------|
| Product type designation | AI Energy Meter 480VAC ST |
| Firmware version | V4.0 |
| usable BaseUnits | BU type D0, BU20-P12+A0+0B |
| Product function | |
| • Voltage measurement | Yes |
| • Current measurement | Yes |
| • Energy measurement | Yes |
| • Frequency measurement | Yes |
| • Power measurement | Yes |
| • Active power measurement | Yes |
| • Reactive power measurement | Yes |
| • I&M data | Yes; I&M0 to I&M3 |
| • Isochronous mode | No |
| Engineering with | |
| • STEP 7 TIA Portal configurable/integrated as of version | V13 SP1 |
| • STEP 7 configurable/integrated as of version | V5.5 SP4 and higher |
| • PROFIBUS as of GSD version/GSD revision | GSD Revision 5 |

| | |
|---|---|
| • PROFINET as of GSD version/GSD revision | V2.3 |
| Operating mode | |
| • Acyclic measured value access | Yes |
| • Fixed measured value sets | Yes |
| • Freely definable measured value sets | Yes |
| CiR – Configuration in RUN | |
| Reparameterization possible in RUN | Yes |
| Calibration possible in RUN | Yes |
| Installation type/mounting | |
| Mounting position | Any |
| Supply voltage | |
| Design of the power supply | Supply via voltage measurement channel L1 |
| Type of supply voltage | AC 100 - 277 V |
| permissible range, lower limit (AC) | 90 V |
| permissible range, upper limit (AC) | 293 V |
| Line frequency | |
| • permissible range, lower limit | 47 Hz |
| • permissible range, upper limit | 63 Hz |
| Power loss | |
| Power loss, typ. | 0.6 W |
| Address area | |
| Address space per module | |
| • Inputs | 256 byte |
| • Outputs | 12 byte |
| Hardware configuration | |
| Automatic encoding | Yes |
| • Mechanical coding element | Yes |
| Selection of BaseUnit for connection variants | |
| • 2-wire connection | BU type D0, BU20-P12+A0+0B |
| Time of day | |
| Operating hours counter | |
| • present | Yes |
| Analog inputs | |
| Cycle time (all channels), typ. | 50 ms; Time for consistent update of all measured and calculated values (cyclic und acyclic data) |
| Cable length | |
| • unshielded, max. | 200 m |
| Analog value generation for the inputs | |
| Measurement principle | Sigma Delta |

| | |
|---|--|
| Sampling frequency, max. | 1 024 kHz |
| Isochronous mode | |
| Isochronous operation (application synchronized up to terminal) | No |
| Interrupts/diagnostics/status information | |
| Alarms | |
| • Diagnostic alarm | Yes |
| • Limit value alarm | Yes |
| • Hardware interrupt | Yes; Monitoring of up to 16 freely selectable process values (exceeding or undershooting of value) |
| Diagnostics indication LED | |
| • Monitoring of the supply voltage (PWR-LED) | Yes |
| • Channel status display | Yes; Green LED |
| • for channel diagnostics | Yes; red Fn LED |
| • for module diagnostics | Yes; green/red DIAG LED |
| Integrated Functions | |
| Measuring functions | |
| • Measuring procedure for voltage measurement | TRMS |
| • Measuring procedure for current measurement | TRMS |
| • Type of measured value acquisition | seamless |
| • Curve shape of voltage | Sinusoidal or distorted |
| • Buffering of measured variables | Yes |
| • Parameter length | 74 byte |
| • Bandwidth of measured value acquisition | 2 kHz; Harmonics: 39 / 50 Hz, 32 / 60 Hz |
| Measuring range | |
| — Frequency measurement, min. | 45 Hz |
| — Frequency measurement, max. | 65 Hz |
| Measuring inputs for voltage | |
| — Measurable line voltage between phase and neutral conductor | 277 V |
| — Measurable line voltage between the line conductors | 480 V |
| — Measurable line voltage between phase and neutral conductor, min. | 90 V |
| — Measurable line voltage between phase and neutral conductor, max. | 293 V |
| — Measurable line voltage between the line conductors, min. | 155 V |
| — Measurable line voltage between the line conductors, max. | 508 V |

- Measurement category for voltage measurement in accordance with IEC 61010-2-030
- Internal resistance line conductor and neutral conductor
- Power consumption per phase
- Impulse voltage resistance 1,2/50 μ s

CAT II; CAT III in case of guaranteed protection level of 1.5 kV

3.4 M Ω

20 mW

1 kV

Measuring inputs for current

- measurable relative current (AC), min.
- measurable relative current (AC), max.
- Continuous current with AC, maximum permissible
- Apparent power consumption per phase for measuring range 5 A
- Rated value short-time withstand current restricted to 1 s
- Input resistance measuring range 0 to 5 A
- Zero point suppression
- Surge strength

1 %; Relative to the secondary rated current 5 A

100 %; Relative to the secondary rated current 5 A

5 A

0.6 V·A

100 A

25 m Ω ; At the terminal

Parameterizable: 2 ... 250 mA, default 50 mA

10 A; for 1 minute

Accuracy class according to IEC 61557-12

- Measured variable voltage
- Measured variable current
- Measured variable apparent power
- Measured variable active power
- Measured variable reactive power
- Measured variable power factor
- Measured variable active energy
- Measured variable reactive energy
- Measured variable neutral current
- Measured variable phase angle
- Measured variable frequency

0,2

0,2

0.5

0.5

1

0.5

0.5

1

0.5; calculated

$\pm 1^\circ$; not covered by IEC 61557-12

0.05

Potential separation

Potential separation channels

- between the channels
- between the channels and backplane bus

No

Yes; 3 700V AC (type test) CAT III

Isolation

Isolation tested with

2 300V AC for 1 min. (type test)

Ambient conditions

Ambient temperature during operation

- horizontal installation, min.
- horizontal installation, max.

0 °C

60 °C

- vertical installation, min. 0 °C
- vertical installation, max. 50 °C

Altitude during operation relating to sea level

- Ambient air temperature-barometric pressure-altitude On request: Ambient temperatures lower than 0 °C (without condensation) and/or installation altitudes greater than 2 000 m

Dimensions

| | |
|--------|-------|
| Width | 20 mm |
| Height | 73 mm |
| Depth | 58 mm |

Weights

| | |
|----------------------------|------|
| Weight (without packaging) | 45 g |
|----------------------------|------|

Other

Data for selecting a voltage transformer

- Secondary side, max. 296 V

Data for selecting a current transformer

- Burden power current transformer x/1A, min. As a function of cable length and cross section, see device manual
- Burden power current transformer x/5A, min. As a function of cable length and cross section, see device manual

last modified: 01/29/2018