

ASPEN PLUS (R) IS A PROPRIETARY PRODUCT OF ASPEN TECHNOLOGY, INC. (ASPENTECH), AND MAY BE USED ONLY UNDER AGREEMENT WITH ASPENTECH. RESTRICTED RIGHTS LEGEND: USE, REPRODUCTION, OR DISCLOSURE BY THE U.S. GOVERNMENT IS SUBJECT TO RESTRICTIONS SET FORTH IN (i) FAR 52.227-14, Alt. III, (ii) FAR 52.227-19, (iii) DFARS 252.227-7013(c)(1)(ii), or (iv) THE ACCOMPANYING LICENSE AGREEMENT, AS APPLICABLE. FOR PURPOSES OF THE FAR, THIS SOFTWARE SHALL BE DEEMED TO BE "UNPUBLISHED" AND LICENSED WITH DISCLOSURE PROHIBITIONS. CONTRACTOR/SUBCONTRACTOR: ASPEN TECHNOLOGY, INC. 20 CROSBY DRIVE, BEDFORD, MA 01730.

TABLE OF CONTENTS

RUN CONTROL SECTION.....	1
RUN CONTROL INFORMATION.....	1
FLOWSHEET SECTION.....	2
FLOWSHEET CONNECTIVITY BY STREAMS.....	2
FLOWSHEET CONNECTIVITY BY BLOCKS.....	2
COMPUTATIONAL SEQUENCE.....	2
OVERALL FLOWSHEET BALANCE.....	2
PHYSICAL PROPERTIES SECTION.....	3
COMPONENTS.....	3
REACTION SECTION.....	4
REACTION: R-1 TYPE: GENERAL.....	4
REACTION: R-12 TYPE: GENERAL.....	4
U-O-S BLOCK SECTION.....	5
BLOCK: PFREAC MODEL: RPLUG.....	5
STREAM SECTION.....	8
CO2 H2 IN OUT.....	8
PROBLEM STATUS SECTION.....	9
BLOCK STATUS.....	9

RUN CONTROL SECTION

RUN CONTROL INFORMATION

THIS COPY OF ASPEN PLUS LICENSED TO CZECH TECHNICAL UNIVERSI

TYPE OF RUN: EDIT

INPUT FILE NAME: _4032zom.inm

INPUT PROBLEM DATA FILE NAME : _4032zom

OUTPUT PROBLEM DATA FILE NAME: _4744dir

LOCATED IN:

PDF SIZE USED FOR INPUT TRANSLATION:

NUMBER OF FILE RECORDS (PSIZE) =	0
NUMBER OF IN-CORE RECORDS =	256
PSIZE NEEDED FOR SIMULATION =	1

CALLING PROGRAM NAME: apmain

LOCATED IN: C:\Program Files (x86)\AspenTech\Aspen Plus V10.0\Engine\XeQ

SIMULATION REQUESTED FOR ENTIRE FLOWSHEET

FLWSHEET SECTION

FLWSHEET CONNECTIVITY BY STREAMS

STREAM	SOURCE	DEST	STREAM	SOURCE	DEST
IN	----	PFREAC	OUT	PFREAC	----

FLWSHEET CONNECTIVITY BY BLOCKS

BLOCK	INLETS	OUTLETS
PFREAC	IN	OUT

COMPUTATIONAL SEQUENCE

SEQUENCE USED WAS:

PFREAC

OVERALL FLWSHEET BALANCE

	*** MASS AND ENERGY BALANCE ***			
	IN	OUT	GENERATION	RELATIVE DIFF.
CONVENTIONAL COMPONENTS				
(KMOL/HR)				
METHA-01	0.00000	0.199328	0.199328	0.00000
CARBO-01	0.199718	0.390269E-03	-0.199328	0.407149E-16
WATER	0.00000	0.398656	0.398656	0.00000
HYDRO-01	0.798874	0.156108E-02	-0.797313	0.101516E-15
CARBO-02	0.00000	0.00000	0.00000	0.00000
TOTAL BALANCE				
MOLE (KMOL/HR)	0.998592	0.599936	-0.398656	0.00000
MASS (KG/HR)	10.4000	10.4000		0.00000
ENTHALPY (CAL/SEC)	-4633.97	-6987.71		0.336840

*** CO2 EQUIVALENT SUMMARY ***		
FEED STREAMS CO2E	8.78957	KG/HR
PRODUCT STREAMS CO2E	79.9615	KG/HR
NET STREAMS CO2E PRODUCTION	71.1719	KG/HR
UTILITIES CO2E PRODUCTION	0.00000	KG/HR
TOTAL CO2E PRODUCTION	71.1719	KG/HR

PHYSICAL PROPERTIES SECTION

COMPONENTS

ID	TYPE	ALIAS	NAME
METHA-01	C	CH4	METHANE
CARBO-01	C	CO2	CARBON-DIOXIDE
WATER	C	H2O	WATER
HYDRO-01	C	H2	HYDROGEN
CARBO-02	C	CO	CARBON-MONOXIDE

REACTION SECTION

REACTION: R-1 TYPE: GENERAL

Unit operations referencing this reaction model:

Reactor Name: PFREAC Block Type: RPLUG

REACTION: R-12 TYPE: GENERAL

Unit operations referencing this reaction model:

Reactor Name: PFREAC Block Type: RPLUG

U-O-S BLOCK SECTION

BLOCK: PFREAC MODEL: RPLUG

INLET STREAM: IN
 OUTLET STREAM: OUT
 PROPERTY OPTION SET: RKSMHV2 RKS-MHV2 EQUATION OF STATE

*** MASS AND ENERGY BALANCE ***

	IN	OUT	GENERATION	RELATIVE DIFF.
TOTAL BALANCE				
MOLE (KMOL/HR)	0.998592	0.599936	-0.398656	0.00000
MASS (KG/HR)	10.4000	10.4000		0.00000
ENTHALPY (CAL/SEC)	-4633.97	-6987.71		0.336840

*** CO2 EQUIVALENT SUMMARY ***

FEED STREAMS CO2E	8.78957	KG/HR
PRODUCT STREAMS CO2E	79.9615	KG/HR
NET STREAMS CO2E PRODUCTION	71.1719	KG/HR
UTILITIES CO2E PRODUCTION	0.00000	KG/HR
TOTAL CO2E PRODUCTION	71.1719	KG/HR

*** INPUT DATA ***

REACTOR TYPE:

SPECIFIED TEMPERATURE
 TWO-PHASE
 REACTOR TUBE LENGTH METER 1.0000
 REACTOR DIAMETER METER 0.30000
 REACTOR RISE METER 0.0000
 NUMBER OF REACTOR TUBES 1
 REACTOR VOLUME L 70.686
 PRESSURE DROP OPTION: SPECIFIED
 HOLDUP OPTION: NO-SLIP
 ERROR TOLERANCE 0.10000E-03
 INTEGRATION METHOD GEAR
 CORRECTOR METHOD NEWTON
 INITIAL STEP SIZE FACTOR 0.10000E-01
 CORRECTOR TOLERANCE FACTOR 0.10000
 MAXIMUM NUMBER OF STEPS 1000

CONSTANT REACTOR TEMPERATURE SET TO THE (MIXED)
 INLET PROCESS STREAM TEMPERATURE OF 299.90 C

REACTION PARAGRAPH ID: R-12 TYPE: GENERAL
 GLOBAL BASES:
 KBASIS MOLE-GAMMA
 CBASIS MOLARITY
 SBASIS GLOBAL

U-O-S BLOCK SECTION

BLOCK: PFREAC MODEL: RPLUG (CONTINUED)
 STOICHIOMETRY:

```

REACTION NUMBER:      1
SUBSTREAM: MIXED
METHA-01  1.0000    CARBO-01  -1.0000    WATER  2.0000    HYDRO-01  -
4.0000

REACTION NUMBER:      2
SUBSTREAM: MIXED
CARBO-01  -1.0000    WATER  1.0000    HYDRO-01  -1.0000    CARBO-02
1.0000

REACTION NUMBER:      3
SUBSTREAM: MIXED
METHA-01  1.0000    WATER  1.0000    HYDRO-01  -3.0000    CARBO-02  -
1.0000
    
```

REAC-DATA ENTRIES:

REACTION NO	TYPE	PHASE	DELT C	BASIS
1	KINETIC	V	200.00	MOLEFRAC
2	KINETIC	V	900.00	MOLEFRAC
3	KINETIC	V	300.00	MOLEFRAC

*** RESULTS ***

REACTOR DUTY	CAL/SEC	-2353.7
RESIDENCE TIME	HR	0.12441E-01
REACTOR MINIMUM TEMPERATURE	C	299.90
REACTOR MAXIMUM TEMPERATURE	C	299.90

*** RESULTS PROFILE (PROCESS STREAM) ***

LENGTH METER	PRESSURE BAR	TEMPERATURE C	VAPOR FRAC	RES-TIME HR
0.0000	5.0000	299.90	1.0000	0.0000
0.10000	5.0000	299.90	1.0000	0.12415E-02
0.20000	5.0000	299.90	1.0000	0.24859E-02
0.30000	5.0000	299.90	1.0000	0.37302E-02
0.40000	5.0000	299.90	1.0000	0.49745E-02
0.50000	5.0000	299.90	1.0000	0.62189E-02
0.60000	5.0000	299.90	1.0000	0.74632E-02
0.70000	5.0000	299.90	1.0000	0.87076E-02
0.80000	5.0000	299.90	1.0000	0.99519E-02
0.90000	5.0000	299.90	1.0000	0.11196E-01
1.0000	5.0000	299.90	1.0000	0.12441E-01

LENGTH METER	DUTY CAL/SEC	LIQUID HOLDUP
0.0000	0.0000	0.0000
0.10000	-2353.7	0.0000
0.20000	-2353.7	0.0000
0.30000	-2353.7	0.0000
0.40000	-2353.7	0.0000
0.50000	-2353.7	0.0000
0.60000	-2353.7	0.0000
0.70000	-2353.7	0.0000
0.80000	-2353.7	0.0000
0.90000	-2353.7	0.0000
1.0000	-2353.7	0.0000

U-O-S BLOCK SECTION

BLOCK: PFREAC MODEL: RPLUG (CONTINUED)

*** TOTAL MOLE FRACTION PROFILE (PROCESS STREAM) ***

LENGTH METER	METHA-01	CARBO-01	WATER	HYDRO-01
0.0000	0.0000	0.20000	0.0000	0.80000
0.10000	0.33225	0.65052E-03	0.66450	0.26021E-02
0.20000	0.33225	0.65052E-03	0.66450	0.26021E-02
0.30000	0.33225	0.65052E-03	0.66450	0.26021E-02
0.40000	0.33225	0.65052E-03	0.66450	0.26021E-02
0.50000	0.33225	0.65052E-03	0.66450	0.26021E-02
0.60000	0.33225	0.65052E-03	0.66450	0.26021E-02
0.70000	0.33225	0.65052E-03	0.66450	0.26021E-02
0.80000	0.33225	0.65052E-03	0.66450	0.26021E-02
0.90000	0.33225	0.65052E-03	0.66450	0.26021E-02
1.0000	0.33225	0.65052E-03	0.66450	0.26021E-02

*** TOTAL MASS FRACTION PROFILE (PROCESS STREAM) ***

LENGTH METER	METHA-01	CARBO-01	WATER	HYDRO-01
0.0000	0.0000	0.84515	0.0000	0.15485
0.10000	0.30748	0.16515E-02	0.69057	0.30259E-03
0.20000	0.30748	0.16515E-02	0.69057	0.30259E-03
0.30000	0.30748	0.16515E-02	0.69057	0.30259E-03
0.40000	0.30748	0.16515E-02	0.69057	0.30259E-03
0.50000	0.30748	0.16515E-02	0.69057	0.30259E-03
0.60000	0.30748	0.16515E-02	0.69057	0.30259E-03
0.70000	0.30748	0.16515E-02	0.69057	0.30259E-03
0.80000	0.30748	0.16515E-02	0.69057	0.30259E-03
0.90000	0.30748	0.16515E-02	0.69057	0.30259E-03
1.0000	0.30748	0.16515E-02	0.69057	0.30259E-03

STREAM SECTION

CO2 H2 IN OUT

STREAM ID	CO2	H2	IN	OUT
FROM :	----	----	----	PFREAC
TO :	----	----	PFREAC	----
SUBSTREAM: MIXED				
PHASE:	VAPOR	VAPOR	VAPOR	VAPOR
COMPONENTS: KMOL/HR				
METHA-01	0.0	0.0	0.0	0.1993
CARBO-01	0.1000	0.0	0.1997	3.9027-04
WATER	0.0	0.0	0.0	0.3987
HYDRO-01	0.0	0.4000	0.7989	1.5611-03
CARBO-02	0.0	0.0	0.0	0.0
TOTAL FLOW:				
KMOL/HR	0.1000	0.4000	0.9986	0.5999
KG/HR	4.4010	0.8064	10.4000	10.4000
L/MIN	21.4616	85.8304	79.5424	94.6761
STATE VARIABLES:				
TEMP C	500.0000	500.0000	299.9000	299.8962
PRES BAR	5.0000	5.0000	10.0000	5.0000
VFRAC	1.0000	1.0000	1.0000	1.0000
LFRAC	0.0	0.0	0.0	0.0
SFRAC	0.0	0.0	0.0	0.0
ENTHALPY:				
CAL/MOL	-8.8871+04	3323.1509	-1.6706+04	-4.1931+04
CAL/GM	-2019.3382	1648.4865	-1604.0657	-2418.8221
CAL/SEC	-2468.6298	369.2390	-4633.9676	-6987.7083
ENTROPY:				
CAL/MOL-K	7.5482	3.4830	1.5318	-9.5754
CAL/GM-K	0.1715	1.7278	0.1471	-0.5524
DENSITY:				
MOL/CC	7.7658-05	7.7673-05	2.0924-04	1.0561-04
GM/CC	3.4177-03	1.5658-04	2.1791-03	1.8308-03
AVG MW	44.0098	2.0159	10.4147	17.3352

PROBLEM STATUS SECTION

BLOCK STATUS

```
*****  
*                                                                 *  
* Calculations were completed normally                          *  
*                                                                 *  
* All Unit Operation blocks were completed normally            *  
*                                                                 *  
* All streams were flashed normally                             *  
*                                                                 *  
*****
```