



LEGEND:

| TYPE | NAME OF ROOM | AREA m ² | FLOORING |
|------|----------------|---|-------------------|
| 0.01 | STAIRS AREA | 22.28 m ² | POLISHED CONCRETE |
| 0.02 | STORE | 8.35 m ² | POLISHED CONCRETE |
| 0.03 | STORE | 8.35 m ² | POLISHED CONCRETE |
| 0.04 | STORE | 8.35 m ² | POLISHED CONCRETE |
| 0.05 | STORE | 8.35 m ² | POLISHED CONCRETE |
| 0.06 | STORE | 8.35 m ² | POLISHED CONCRETE |
| 0.07 | STORE | 7.95 m ² | POLISHED CONCRETE |
| 0.08 | STORE | 7.95 m ² | POLISHED CONCRETE |
| 0.09 | STORE | 7.95 m ² | POLISHED CONCRETE |
| 0.10 | STORE | 7.95 m ² | POLISHED CONCRETE |
| 0.11 | STORE | 7.95 m ² | POLISHED CONCRETE |
| 0.12 | STORE | 7.95 m ² | POLISHED CONCRETE |
| 0.13 | STORE | 7.95 m ² | POLISHED CONCRETE |
| 0.14 | STORE | 8.35 m ² | POLISHED CONCRETE |
| 0.15 | STORE | 8.35 m ² | POLISHED CONCRETE |
| 0.16 | STORE | 8.35 m ² | POLISHED CONCRETE |
| 0.17 | STORE | 8.35 m ² | POLISHED CONCRETE |
| 0.18 | STORE | 8.35 m ² | POLISHED CONCRETE |
| 0.19 | STORE | 8.35 m ² | POLISHED CONCRETE |
| 0.20 | TECHNICAL ROOM | 30.33 m ² | POLISHED CONCRETE |
| 0.21 | UPS | 19.08 m ² | POLISHED CONCRETE |
| P | PARKING SPOTS | NORMAL 12.5m ² INVALID 19.5m ² | POLISHED CONCRETE |

LEGEND OF MATERIALS :

- REINFORCED CONCRETE C30/37
- TERRAIN
- THERMAL INSULATION XPS 130mm
- WATERPROOF BITUMEM
- POROTHERM 11.5 Aku 497/115/238mm
- POROTHERM 8 Aku 497/80/238mm
- W4 POROTHERM 8 Aku 497/80/238mm (2200) mm
- D1 EW 30 DPT ALUMINUM DOOR
- D2 ALUMINUM DOOR
- D3 EW 30 DPT ALUMINUM DOOR
- D7 EI 30 DPT -C-S-O GLASS DOOR
- S0 SHAFTS
- H HYDRANT

| | | |
|-------------------------------------|---|---|
| Designed by: Bashar Alachkar | Checked by: Ing. Malila Noori, Ph.D. | Czech Technical University 1:50 2020-2021 |
| Drawing: Underground plan view | | |
| Subject: 124BPRO – Bachelor Project | | |

