

CZECH TECHNICAL UNIVERSITY IN PRAGUE



DOCTORAL THESIS STATEMENT

Czech Technical University in Prague
Faculty of Electrical Engineering
Department of Cybernetics

Zuzana Kúkelová

Algebraic Methods in Computer Vision

Ph.D. Programme: Electrical Engineering and Information Technology, P2612

Branch of study: Mathematical Engineering, 3901V021

Doctoral thesis statement for obtaining the academic title of “Doctor”,
abbreviated to “Ph.D.”

Prague, February 2013

The doctoral thesis was produced in part-time manner during Ph.D. study at the Center for Machine Perception of the Department of Cybernetics of the Faculty of Electrical Engineering of the CTU in Prague.

Candidate: RNDr. Zuzana Kúkelová
Department of Cybernetics
Faculty of Electrical Engineering of the CTU in Prague

Supervisor: Ing. Tomáš Pajdla, Ph.D.
Department of Cybernetics
Faculty of Electrical Engineering of the CTU in Prague

Opponents:
.....
.....

The doctoral thesis statement was distributed on

The defence of the doctoral thesis will be held on at a.m./p.m. before the Board for the Defence of the Doctoral Thesis in the branch of study Mathematical Engineering, in the meeting room No. of the Faculty of Electrical Engineering of the CTU in Prague.

Those interested may get acquainted with the doctoral thesis concerned at the Dean Office of the Faculty of Electrical Engineering of the CTU in Prague, at the Department for Science and Research, Technická 2, 166 27 Prague 6.

.....
Chairman of the Board for the Defence of the Doctoral Thesis
in the branch of study Mathematical Engineering
Department of Mathematics, Technická 2, 166 27 Prague 6.

Contents

1	Problem Formulation	2
2	Contributions	3
3	State of the Art	6
4	Specialized algebraic methods for solving systems of polynomial equations	8
5	Automatic generator of minimal problems solvers	11
6	Minimal problems	12
7	Conclusion	17

Keywords: Gröbner basis, resultants, polynomial eigenvalue problems, minimal problems, relative pose problems, radial distortion.

Note: Full text of the thesis is available at <ftp://cmp.felk.cvut.cz/pub/cmp/articles/kukelova/Kukelova-phd-thesis.pdf>

1 Problem Formulation

Many important problems in computer vision as well as in other fields can be formulated using systems of polynomial equations. Examples of problems that require solving complex systems of non-linear polynomial equations are problems of estimating camera geometry, such as relative or absolute camera pose problems. These problems have a broad range of applications, e.g., in structure-from-motion and 3D reconstruction [1, 20, 35, 36], recognition [28, 29], video-based rendering [4], robotics, and augmented reality.

The problem of solving systems of non-linear polynomial equations is a very old problem with many different well-studied solution methods. In general, the methods can be divided into numerical and algebraic methods. In this thesis we focus on algebraic methods. We review two classes of standard algebraic methods, i.e. the Gröbner basis and the resultant based methods. These methods are very useful mathematical methods but since they are general, i.e. they were developed for general systems of polynomial equations, they are usually not sufficiently efficient for systems which appear in computer vision problems.

It is because problems like estimating relative or absolute pose of a camera are usually parts of some large systems, e.g., structure-from-motion pipelines or recognition systems, which require high or even real-time performance. Moreover, the input measurements used for the computation are often contaminated with a large errors. Therefore, these problems have to be solved for many different inputs to find the “best solution”, i.e. the solution consistent with as many measurements as possible, e.g., when using in RANSAC-based algorithms [16].

This means that computer vision problems usually require very fast, efficient, and numerically stable solvers which are able to solve many instances of one problem, i.e. many systems of polynomial equations of “one form” only with different “non-degenerate” coefficients, in milliseconds. Unfortunately, this requirement usually cannot be fulfilled by using standard general methods for solving systems of polynomial equations.

Therefore, in recent years various specific algorithms based on algebraic geometry concepts have been proposed to achieve numerical robustness and computational efficiency when solving computer vision problems. The main property of these algorithms is that they use a specific structure of a system of polynomial equations arising from a particular problem to efficiently solve this problem only.

Recently, many efficient specific algorithms for solving various computer vision problems have been proposed [32, 40, 37, 41, 42, 38, 33, 8, 31, 30, 8, 9, 7, 21]. They are mostly based on standard algebraic methods and designed manually for a particular problem. This manual design usually requires

deeper knowledge of algebraic geometry and considerable amount of craft, which makes the process of generation of these specific solvers complex and virtually impenetrable for a non-specialist. Moreover, for some of these problems it is not clear how their solvers were created and therefore non-specialists often use them as black boxes; they are not able to reimplement them, improve them, or create similar solvers for their own new problems.

2 Contributions

This thesis focuses on algebraic methods for solving systems of polynomial equations appearing especially in computer vision problems. Its main goal is to improve algebraic based methods previously used to manually create efficient solvers to some computer vision problems, automate these methods, and apply them to efficiently solve previously unsolved minimal computer vision problems.

The contribution of the proposed thesis can be divided into three main groups:

- **Algebraic methods for solving systems of polynomial equations**

The first group of contributions of this thesis are modifications of two standard algebraic techniques for solving systems of polynomial equations; the Gröbner basis and the resultant based techniques. These modifications enable the creation of efficient specific solvers for particular problems, i.e. particular systems of polynomial equations.

The main difference between the proposed specialized methods and general methods is that the specialized methods use the structure of the system of polynomial equations representing a particular problem to design a specific efficient solver for this problem.

These specialized methods consist of two phases. In the first phase some preprocessing and computations common to all considered instances of the given problem are performed and an efficient specific solver is constructed. For a particular problem this phase needs to be performed only once.

In the second phase, the efficient specific solver is used to solve concrete instances of the particular problem. This specific efficient solver is not general and solves only systems of polynomial equations of one form, i.e. systems which coefficients always generate the same “path” to the solution. However, the specific solver is faster than a general solver and suitable for applications which appear in computer vision.

In the case of the specialized Gröbner basis method we summarize and extend the Gröbner basis method used to manually create solvers to some previously solved computer vision problems [37, 38, 41, 40]. Thanks to the proposed extensions, e.g., the identification of the form of necessary polynomials, new strategies for generating these polynomials, and new procedures for removing unnecessary polynomials, we are able to create smaller, more efficient, and more stable solvers than the previously manually created solvers [37, 38, 41, 40]. Moreover, all these extensions can be easily automated and therefore the presented specialized Gröbner basis method can be used even by non-experts to solve technical problems leading to systems of polynomial equations.

The second proposed specialized method is based on hidden variable resultants and polynomial eigenvalue problems [3]. In this thesis we propose several strategies for transforming the initial system of polynomial equations to polynomial eigenvalue problem [3] and for reducing the size of this problem. In this way we are able to create efficient and numerically stable specific solvers for many problems appearing in computer vision. Again, this method can be easily automated.

- **Automatic generator of Gröbner basis solvers**

Since the presented specialized Gröbner basis method requires non-trivial knowledge of algebraic geometry from its user, we propose an automatic method for generating Gröbner basis solvers which could be used even by non-experts to easily solve problems leading to systems of polynomial equations. The input to our solver generator is a system of polynomial equations with a finite number of solutions. The output of our solver generator is a Matlab code that computes solutions to this system for arbitrary “non-degenerate” coefficients. Generating solvers automatically open possibilities for solving more complicated problems that could not be handled manually or solving existing problems in a better and more efficient way. We demonstrate that our automatic generator constructs efficient and numerically stable solvers that are comparable or better than known manually constructed solvers in terms of computational time, space requirements, and numerical stability.

- **Solutions to minimal problems in computer vision**

To demonstrate the usefulness of the proposed specialized techniques for solving systems of polynomial equations and the usefulness of our automatic generator of Gröbner basis solvers, we provide efficient solutions to several important relative pose problems. In this thesis we describe

solutions to five minimal problems which haven't been solved before:

1. the problem of simultaneous estimation of the fundamental matrix and a common radial distortion parameter for two uncalibrated cameras from eight image point correspondences,
2. the problem of simultaneous estimation of the essential matrix and a common radial distortion parameter for two partially calibrated cameras and six image point correspondences,
3. the problem of simultaneous estimation of the fundamental matrix and two radial distortion parameters for two different uncalibrated cameras from nine image point correspondences,
4. the 6-point relative pose problem for one fully calibrated and one up to focal length calibrated camera, and
5. the problem of estimating epipolar geometry and unknown focal length from images of four points lying on a plane and one off-the-plane point, i.e. the “plane + parallax” problem for cameras with unknown focal length.

Our solutions to these five new minimal problems are based on the specialized Gröbner basis method and are generated using our automatic generator of Gröbner basis solvers. Moreover, for the “8-point radial distortion problem”, the “6-point problem for one fully calibrated and one up to focal length calibrated camera” and for the “plane + parallax + focal length” problem, we also propose the “polynomial eigenvalue solutions” based on the specialized resultant based method.

Beside these solutions to previously unsolved minimal problems, we provide new solutions to two well known important relative pose problems:

6. the 5-point relative pose problem for two calibrated cameras, and
7. the 6-point relative pose problem for two cameras with unknown equal focal length.

We show that these two problems lead to polynomial equations that can be solved robustly and efficiently as cubic and quadratic eigenvalue problems. These new solutions are fast, and in the case of the 6-pt solver, also slightly more stable than the existing solution [40]. In the case of the “6-point equal focal length problem”, we also propose a new Gröbner basis solution generated by our automatic generator and we show that this solution is slightly more stable and also faster than previous Gröbner basis solutions to this problem [40, 8].

3 State of the Art

Solving systems of polynomial equations

Solving systems of polynomial equations is a classical problem with many applications, e.g., in computer vision, robotics, computer graphics and geometric modeling. This problem has its origin in ancient Greece and China. Therefore it is not surprising that there exists a large number of methods for solving systems of polynomial equations.

We can divide them according to several criteria. One possible and very simple division is the division into numerical and symbolic methods. In this thesis we focus on symbolic (algebraic) methods.

The main idea of symbolic methods for solving systems of polynomial equations is to eliminate variables from the system, and in this way, to reduce the problem to finding the roots of univariate polynomials. These methods have their origins in algebraic geometry and are therefore sometimes called algebraic methods or symbolic elimination methods.

In general, the algorithms for symbolic methods are efficient for smaller systems. For bigger systems, most of the general algorithms based on algebraic methods suffer from accuracy or efficiency problems. It is because these algorithms often require exact or multiple-precision arithmetic, which slows them down considerably.

The symbolic methods may be divided into:

1. resultant methods,
2. Gröbner bases, and
3. Ritt-Wu's methods.

Since these symbolic methods are well studied mathematical methods there are many excellent books and papers available on this topic including theory and applications. An overview of classical symbolic methods can be found in [23, 10, 11]. [34] is a nice survey of these methods with examples of their applications in computer vision.

Implementations of Gröbner bases and resultants algorithms and many algorithms based on their applications are contained in all of the current mathematical software systems like Mathematica, Maple, Magma, Axiom, Derive, Reduce, etc. Also, special software systems exist that are mainly based on the Gröbner bases technique, for example, CoCoA [2], Macaulay [19], Singular [13].

Minimal problems

Many problems in computer vision, especially problems of computing camera geometry, can be formulated using systems of polynomial equations. Such systems of polynomial equations can have an infinite number of solutions, i.e. are under-determined, no solution, i.e. are over-determined, or these systems can have a finite number of solutions.

In the case of problems of computing camera geometry, the number of equations in the system and the corresponding number of solutions depend on the number of geometric constraints and the number of input data (usually 2D-2D, 2D-3D or 3D-3D point or line correspondences) used to formulate the problem. The problems solved from a minimal number of input data and using all the possible geometric constraints that lead to a finite number of solutions are often called “minimal problems” or “minimal cases”.

Various minimal problems have been recently studied extensively in computer vision [43, 32, 40, 37, 41, 42, 38, 33, 8, 31, 30]. It is because a smaller number of input data is less likely to contain incorrect inputs and therefore considerably reduces the number of samples needed in RANSAC-based algorithms [16], which are widely used in many applications.

In this thesis we add several new minimal problem solutions to the family of recently solved minimal problems [16, 32, 33, 33, 40, 37, 18]. All these problems lead to systems of polynomial equations. For some problems, like the perspective three point problem, these systems are not so complicated and the solution to them is known for years and can be found using some manipulations and tricks in a closed form [16]. However, more often these problems lead to very complex systems of non-linear polynomial equations and numerical or symbolic methods based on resultants or Gröbner bases need to be used to solve them.

Macaulay’s resultant was, for example, used in [43] to solve the problem of estimating absolute pose of a camera with unknown focal length from four 2D-to-3D correspondences and the problem of estimating absolute pose of a camera with unknown focal length and unknown principal point from five 2D-to-3D correspondences. Sparse resultants were used to solve the well know five point relative pose problem [14]. This five point problem [31], as well as the six point relative pose problem for camera with unknown focal length [30], were solved also using the hidden variable resultant based method [10].

Unfortunately, standard symbolic methods for solving general systems of polynomial equations, like the Buchberger’s algorithm for computing Gröbner bases [10], or the previously described standard resultant based solutions [43, 14, 31, 30] may be very inefficient when solving minimal problems in computer

vision.

It is because minimal problems are usually parts of some large systems which require high or even real-time performance, e.g., structure-from-motion pipelines or recognition systems, and due to incorrect inputs and noise need to be solved for many different inputs in RANSAC-like algorithms [16] in milliseconds.

Thus, in recent years, various specific algorithms based on algebraic geometry concepts have been proposed focusing on numerical robustness and computational efficiency when solving minimal problems. The main property of these algorithms is that they use specific properties of a system of polynomial equations arising from a particular problem to efficiently solve this problem only.

Stewénius [37] proposed a method for constructing solvers for problems leading to systems of polynomial equations based on Gröbner bases and multiplication matrices. The resulting solvers are based on facts that in a class of problems the “path” to the Gröbner basis is always the same and that algorithms computing Gröbner bases can be realized using Gauss-Jordan elimination [15]. Based on these facts effective and practical algorithms for solving minimal problems can be designed. Using this method Stewénius et al. solved problems such as the five point relative pose problem [38], the six point relative pose problem for a camera with unknown constant focal length [40], the six point generalized camera problem [41], the nine point problem for estimating para-catadioptric fundamental matrices [18], the minimal problem for infinitesimal camera motion [39] as well as some other minimal problems [37].

A similar Gröbner basis method was used by other authors to solve the 3-point problem for panorama stitching for camera with unknown focal length and radial distortion [7], the absolute pose problem for camera with unknown focal length and radial distortion [21] and the 3-point relative pose problem for camera with known vertical direction [22].

Since for larger systems numerical problems of Gröbner basis solvers may appear [7], various techniques for improving the numerical stability of such solvers in computer vision have been proposed in [8, 9, 6].

4 Specialized algebraic methods for solving systems of polynomial equations

In this thesis we suggest modifications to two general algebraic methods for solving systems of polynomial equations; the Gröbner basis and the resultant based methods, which are suitable for many computer vision problems.

The main difference between the proposed specialized methods and general methods is that the specialized methods use the structure of the system of polynomial equations representing a particular problem to design a specific efficient solver for this problem.

These specialized methods consist of two phases. In the first phase some pre-processing and computations common to all considered instances of the given problem are performed and an efficient specific solver is constructed. For a particular problem this phase needs to be performed only once, therefore, we will call it the “offline phase”.

In the second “online phase”, the efficient specific solver is used to solve concrete instances of the particular problem.

Specialized Gröbner basis method

Our specialized Gröbner basis method follows and extends ideas of the method proposed and used by Stewenius to manually create Gröbner basis solvers to some computer vision problems [37, 38, 41, 40].

The most important improvements are:

1. identification of the form of the polynomials necessary for constructing a multiplication matrix,
2. several strategies for generating polynomials from the ideal, and
3. new methods for removing unnecessary polynomials and monomials from the found “elimination template”.

Thanks to these improvements we are able to create efficient specific Gröbner basis solvers for particular problems which are usually smaller, more efficient, and more stable than the manually created ones. Moreover, our specialized Gröbner basis method can be easily automated and therefore used even by non-experts to solve technical problems leading to systems of polynomial equations. Next, we describe the basic steps of this specialized Gröbner basis method.

Assume a set S of instances of a particular problem which are all “in the form” of one system of polynomial equations $F = \{f_1 = f_2 = \dots = f_m = 0\}$. A solver for solving instances belonging to the set S can be created in the following way:

Offline phase

1. Fix a monomial ordering \succ (The graded reverse lexicographical ordering is often good).

2. Find the basis B of the quotient ring $A = \mathbb{C}[x_1, \dots, x_n]/I$ as the basis which repeatedly appears for several different (usually random) choices of coefficients of input equations that all belong to the set S . Do computations in a suitably chosen finite prime field to speed them up and to avoid numerical problems.
3. Choose a strategy for generating polynomials from the ideal I generated by input polynomials f_1, \dots, f_m .
4. For a suitably chosen monomial \mathbf{x}^β and the selected strategy for generating polynomials from the ideal I , find a “path” from the initial polynomials f_1, \dots, f_m to polynomials q_i that are necessary for constructing the multiplication matrix $M_{\mathbf{x}^\beta}$. Do this by systematically generating higher order polynomials from the initial polynomials using the selected strategy. Again, do computations in a finite prime field and with some “non-degenerate” coefficients from S (usually random).
5. Remove “unnecessary” polynomials, i.e. polynomials that are not necessary for generating polynomials q_i , from all generated polynomials.
6. Detect “unnecessary monomials”, i.e. monomials that do not affect the polynomials q_i .
7. The remaining polynomials, together with the way of how they should be eliminated, form the resulting “elimination template” for the “online” solver.

The final “online” solver for solving all systems of polynomial equations “in the form” of the “representing” system F consists of these steps:

Online phase

1. Using the “elimination template” found in the offline phase, generate all necessary polynomials q_i from the initial polynomials with coefficients from \mathbb{C} .
2. Construct the multiplication matrix $M_{\mathbf{x}^\beta}$ from coefficients of polynomials q_i .
3. Find the solutions of the input system of polynomial equations by finding eigenvectors of the multiplication matrix $M_{\mathbf{x}^\beta}$ or by computing roots of the characteristic polynomial [12, 14] of $M_{\mathbf{x}^\beta}$.

Specialized resultant based method

The second proposed specialized method is the method based on the hidden variable resultants [10] and the polynomial eigenvalue problems (PEP) [3]. The main idea of this method is the transformation of the initial system of polynomial equations to the polynomial eigenvalue problem [3]

$$(\alpha^l \mathbf{C}_l + \alpha^{l-1} \mathbf{C}_{l-1} + \dots + \alpha \mathbf{C}_1 + \mathbf{C}_0) \mathbf{v} = \mathbf{0}, \quad (1)$$

where \mathbf{v} is a vector of monomials in all variables except for a selected variable α and \mathbf{C}_j 's are $n \times n$ coefficient matrices. This is done by “hiding” the variable α in the coefficient field and generating polynomials using the modified Macaulay’s method for computing resultants. Therefore we also call this specialized resultant based method the polynomial eigenvalue method.

Similarly to the case of the specialized Gröbner basis method this resultant based method can be divided into the “offline” and the “online” phase.

To create efficient robust specific polynomial eigenvalue solvers we propose:

1. several strategies for transforming a system of polynomial equations to a PEP,
2. a method for removing unnecessary polynomials from the polynomial eigenvalue formulation of the problem, and
3. a method for removing zero eigenvalues from the polynomial eigenvalue formulation of the problem.

Thanks to these proposed strategies we are able to create efficient and numerically stable polynomial eigenvalue solvers to many computer vision problems.

5 Automatic generator of minimal problems solvers

In this thesis we propose an automatic generator of Gröbner basis solvers which is based on the proposed specialized Gröbner basis method. This automatic generator searches for an “elimination path” for a given system of polynomial equations F and using this path produces an efficient solver for all instances of the input problem that would lead to the same “elimination path”, i.e. all systems of polynomial equations that are “in the form” of the input system F . It is a number of valid paths the generator can find. The final choice of the path is determined by the particular coefficients of F .




Figure 1: Block diagram of the basic moduls of the automatic generator.

The input to our automatic generator is a system of polynomial equations F that we want to solve, i.e. a system representing considered instances of a particular problem, with concrete coefficients from \mathbb{Z}_p that determine the particular “elimination path”. For many problems, the “interesting” solutions can be obtained with almost any, i.e. random, choice of coefficients of F . Therefore, we use random values from \mathbb{Z}_p as default coefficients. The output of the generator is the Matlab or Maple code that returns solutions to all systems of polynomial equations “in the form” of the input system F , with specific coefficients from \mathbb{C} . During the online computations, only the resulting solver is called.

This automatic generator can be used even by non-experts to create solvers for new or existing problems and usually results in smaller, more efficient and more stable solvers than the manually created ones. Moreover, generating solvers automatically opens possibilities to solve more complicated problems which could not be handled manually.

Our automatic generator consists of several modules (Figure 1). Since all these modules are independent, they can be further improved or replaced by more efficient implementations.

6 Minimal problems

We demonstrate the usefulness of both the proposed specialized techniques and the automatic generator by providing new efficient solutions to several important relative pose problems, most of which were not solved before.

8-point radial distortion problem

Let us start with the problem is the problem of simultaneous estimation of the fundamental matrix and a common radial distortion parameter, given by the




Figure 2: (a) Log_{10} relative error of the radial distortion parameter λ obtained by selecting the real root closest to the ground truth value $\lambda_{th} = -0.2$ for noise free synthetic scene (b) Input image with significant radial distortion. (c) Corrected image using the presented 8-point algorithm.

division model [17], for two uncalibrated cameras from eight image point correspondences. This problem has 16 solutions and was previously solved only for nine image point correspondences [17].

We propose two formulations of this problem, the first resulting in three polynomial equations in three unknowns and the second in seven equations in seven unknowns, and we present three new minimal solutions to these formulations.

Gröbner basis solution of the “7 in 7” formulation. The first Gröbner basis solution is based on the multiple elimination strategy for generating polynomials from an ideal and even though it results in larger solver than the “3 in 3” formulation it has less critical configurations. The final solver consists of four Gauss-Jordan (G-J) eliminations of 49×119 , 154×119 , 106×126 , and 108×126 matrices and eigenvalue computations of a 16×16 matrix.

Gröbner basis solution of the “3 in 3” formulation. The second Gröbner basis solution is based on the single elimination strategy for generating polynomials from an ideal and was generated using our automatic generator. This solver consists of one G-J elimination a 32×48 matrix and eigenvalue computations of a 16×16 matrix.

Polynomial eigenvalue solution of the “3 in 3” formulation. The polynomial eigenvalue solver for this problem needs to compute the inverse of a 10×10 matrix and eigenvalues of a 29×29 matrix.

The numerical stability of all of the three proposed solvers and the two pre-

viously published solvers [17, 8] can be seen in Figure 2 (a) and the results on real-world photographs with significant radial distortion in Figure 2 (b) and (c).

9-point different radial distortion problem

The second problem that we have solved is the problem of simultaneous estimation of the fundamental matrix and two radial distortion parameters for two uncalibrated cameras with different distortions from nine image point correspondences. This minimal problem has 24 solutions and hasn't been solved before.

The Gröbner basis solver for this problem generated using the proposed automatic generator needs to perform one G-J elimination of a 179×203 matrix and to compute eigenvalues of a 24×24 matrix. This solver is smaller than our previous manually created solver [3] which needs to perform LU decomposition of a 393×390 matrix and eigenvalue computations of a 24×24 matrix.

6-point calibrated radial distortion problem

The third radial distortion problem which we have solved is the problem of simultaneous estimation of the essential matrix and a common radial distortion parameter for two partially calibrated cameras and six image point correspondences. This problem results in a quite complicated system of equations with 52 solutions.

The Gröbner basis solver generated using the proposed automatic generator needs to perform one G-J elimination of a 238×290 and to compute eigenvalues of a 52×52 matrix and is smaller than our previously published manually created solver [3].

5-point relative problem

One of the most important relative pose problems is the 5-point relative pose problem for two calibrated cameras.

In this thesis we show that this problem leads to polynomial equations that can be solved robustly and efficiently as a cubic eigenvalue problem. Moreover, our Gröbner basis solver which uses Danilevskii method [12] for computing the characteristic polynomial is almost as fast as specific manually created and optimized "closed-form" state-of-the-art solution [32] and outperforms the state-of-the-art Gröbner basis solution [38].




Figure 3: The \log_{10} relative focal length error for the 6-point equal focal length problem. Here `gb6pt` denotes Stewenius Gröbner basis solver [40], `1elim6pt` - the Gröbner basis solution with single elimination presented in our thesis and `peig6pt` our polynomial eigenvalue solver.

6-point equal focal length problem

In the case of the 6-point relative pose problem for two cameras with unknown equal focal length we propose two new solutions.

The Gröbner basis solver generated using our automatic generator needs to perform G-J elimination of a 31×46 matrix and to compute eigenvalues of a 15×15 matrix.

The polynomial eigenvalue solver needs to compute the inverse of one 10×10 matrix and then to compute eigenvalues of a 20×20 matrix.

Both these new solutions are more stable and faster than previous Gröbner basis solutions to this problem [40, 8]. Using the Danilevskii method [12] for computing the characteristic polynomial our Gröbner basis solution gains more than $8 \times$ speed-up over the fastest available Gröbner basis solutions to this problem [40, 8, 6].

Figure 3 shows the numerical stability of the both proposed solvers, the polynomial eigenvalue solver (Blue), and the Gröbner basis solver (Green), compared to the state-of-the-art Gröbner basis solver [40].

6-point one calibrated camera problem

We also propose new efficient and robust minimal solutions to configuration with one completely calibrated camera and one camera with unknown focal length. We show that this solution can cope with the most unpleasant degeneracies and can be effectively used to reconstruct 3D scenes from collections of




Figure 4: A 3D reconstruction of the Trevi Fountain using our 6-point one calibrated camera problem.

images with a very few (in principle single) images with known focal length(s), e.g., unordered data sets downloaded from the Internet, see Figure 4.

This minimal problem hasn't been solved before and has 9 solutions. Both our minimal solvers for this problem are very simple and efficient.

Our Gröbner basis solver generated using the automatic generator has to perform a single G-J elimination of a 21×30 matrix and to compute eigenvalues of a 9×9 matrix.

The generalized eigenvalue solver for this problem does not perform any elimination; however, it calculates generalized eigenvectors. This involves computation of the inverse of one 10×10 matrix and then eigenvalues of a matrix of the same size.

Plane+parallax problem for cameras with unknown focal length

The final relative pose problem which we have solved is the minimal problem of estimating epipolar geometry and unknown focal length from images of four points lying on a plane and one off-the-plane point. This problem is known as the plane + parallax problem for cameras with unknown focal length and has not been solved before. Such problem is important in situations where a

dominant plane is present in the scene, such as in 3D reconstructions of cities or other man-made objects.

We have once again proposed two efficient robust solutions to this problem. The Gröbner basis solution generated by our automatic generator has to perform a single G-J elimination of a 10×15 matrix and to compute eigenvalues of a 5×5 matrix and the polynomial eigenvalue solution has to compute the inverse of one 4×4 matrix and the eigenvalues of a 8×8 matrix.

7 Conclusion

In this thesis we suggest modifications of two standard algebraic techniques for solving systems of polynomial equations, i.e. the Gröbner basis and the resultant based technique, that are suitable for many computer vision problems.

The proposed specialized methods use the specific structure of a system of polynomial equations representing a particular problem to create an efficient specific solver for solving this problem. Such solver is not general and solves only systems of polynomial equations of one form, i.e. systems “in the form” of the representing system; however, it is faster than general solvers and suitable for applications which appear in computer vision and robotics.

Both presented specialized methods can be easily automated and therefore used even by non-experts to solve technical problems leading to systems of polynomial equations. In this thesis we propose the automatic generator of such efficient specific solvers based on the specialized Gröbner basis method.

We demonstrate the usefulness of the proposed specialized techniques and the automatic generator by providing new efficient and numerical stable solutions to several important relative pose problems, most of which were not solved before. These problems include problems of estimating relative pose and internal parameters of calibrated, partially calibrated (with unknown focal length), or completely uncalibrated perspective or radially distorted cameras observing general scenes or scenes with dominant plane. All these problems can be efficiently used in many applications such as camera localization, structure-from-motion, scene reconstruction, tracking and recognition. The quality of all presented solvers is demonstrated on synthetic and real data.

References

- [1] 2D3. Boujou - <http://www.2d3.com>.
- [2] J. Abbott and A.M. Bigatti. CoCoALib: a c++ library for doing Computations in Commutative Algebra. Available at <http://cocoa.dima.unige.it/cocoalib>.

- [3] Z. Bai, J. Demmel, J. Dongarra, A. Ruhe, and H. Van Der Vorst. *Templates for the solution of algebraic eigenvalue problems: a practical guide*. Society for Industrial and Applied Mathematics, Philadelphia, PA, USA, 2000.
- [4] L. Ballan, G. J. Brostow, J. Puwein, and M. Pollefeys. Unstructured video-based rendering: Interactive exploration of casually captured videos. In *ACM SIGGRAPH'10*, pages 1–11, 2010.
- [5] M. Bujnak, Z. Kukelova, and T. Pajdla. Making Minimal Solvers Fast. In *CVPR'12*, 2012.
- [6] M. Byröd. *Numerical Methods for Geometric Vision: From Minimal to Large Scale Problems*. PhD thesis, Centre for Mathematical Sciences LTH, Lund University, Sweden, 2010.
- [7] M. Byröd, M. Brown, and K. Åström. Minimal solutions for panoramic stitching with radial distortion. In *BMVC'09*, 2009.
- [8] M. Byröd, K. Josephson, and K. Åström. Improving numerical accuracy of gröbner basis polynomial equation solvers. In *ICCV'07*, 2007.
- [9] M. Byröd, K. Josephson, and K. Åström. A column-pivoting based strategy for monomial ordering in numerical gröbner basis calculations. In *ECCV'08*, 2008.
- [10] D. Cox, J. Little, and D. O'Shea. *Using Algebraic Geometry*. Springer, 2nd edition, 2005.
- [11] D.A. Cox, J. Little, and D. O'Shea. *Ideals, Varieties, and Algorithms: An Introduction to Computational Algebraic Geometry and Commutative Algebra*. Undergraduate Texts in Mathematics. Springer, 2010.
- [12] A. M. Danilevskii. The numerical solution of the secular equation (russian). *Matem. sbornik*, 44:169–171, 1937. In Russian.
- [13] G.-M.; Pfister G.; Schönemann H. Decker, W.; Greuel. Singular 3-1-5 — A computer algebra system for polynomial computations. 2012. <http://www.singular.uni-kl.de>.
- [14] I. Z. Emiris. *Sparse elimination and applications in kinematics*. PhD thesis, University of California at Berkeley, Berkeley, CA, USA, 1994.
- [15] J. C. Faugère. A new efficient algorithm for computing gröbner bases (f_4). *Journal of Pure and Applied Algebra*, 139(1-3):61–88, 1999.
- [16] M. A. Fischler and R. C. Bolles. Random sample consensus: a paradigm for model fitting with applications to image analysis and automated cartography. *Commun. ACM*, 24(6):381–395, June 1981.
- [17] A. W. Fitzgibbon. Simultaneous linear estimation of multiple view geometry and lens distortion. 1:125, 2001.
- [18] C. Geyer and H. Stewenius. A nine-point algorithm for estimating para-catadioptric fundamental matrices. In *CVPR'07*, 2007.
- [19] D. R. Grayson and M. E. Stillman. Macaulay2, a software system for research in algebraic geometry, available at <http://www.math.uiuc.edu/Macaulay2/>.
- [20] A. Irschara, C. Zach, J. M. Frahm, and H. Bischof. From structure-from-motion point clouds to fast location recognition. In *CVPR'09*, pages 2599–2606, 2009.
- [21] K. Josephson and M. Byröd. Pose estimation with radial distortion and unknown focal length. In *CVPR'09*, 2009.
- [22] M. Kalantari, A. Hashemi, F. Jung, and J. Pi. Guedon. A new solution to the relative orientation problem using only 3 points and the vertical direction. *Journal of Mathematical Imaging and Vision*, 39(3):259–268, March 2011.

- [23] D. Kapur and Y. N. Lakshman. Elimination methods: An introduction. *Symbolic and Numerical Computation for Artificial Intelligence*, B. Donald et al. (eds.), pages 45–87, 1992.
- [24] Z. Kukelova, M. Bujnak, and T. Pajdla. Automatic generator of minimal problem solvers. In *ECCV'08, Part III*, volume 5304 of *Lecture Notes in Computer Science*, pages 302–315, 2008.
- [25] Z. Kukelova, M. Byröd, K. Josephson, T. Pajdla, and K. Åström. Fast and robust numerical solutions to minimal problems for cameras with radial distortion. *Computer Vision and Image Understanding*, 114(2):234–244, February 2010.
- [26] Z. Kukelova and T. Pajdla. Two minimal problems for cameras with radial distortion. In *OMNIVIS'07*, 2007.
- [27] Zuzana Kukelova and Tomas Pajdla. A minimal solution to the autocalibration of radial distortion. In *CVPR'07*, 2007.
- [28] B. Leibe, N. Cornelis, K. Cornelis, and L. van Gool. Dynamic 3d scene analysis from a moving vehicle. In *CVPR'07*, 2007.
- [29] B. Leibe, K. Schindler, and L. van Gool. Coupled detection and trajectory estimation for multi-object tracking. In *ICCV'07*, 2007.
- [30] H. Li. A simple solution to the six-point two-view focal-length problem. In *ECCV'06 - Part IV*, pages 200–213, 2006.
- [31] H. Li and R. Hartley. Five-point motion estimation made easy. In *ICPR'06*, volume 1, pages 630–633, 2006.
- [32] D. Nistér. An efficient solution to the five-point relative pose problem. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 26(6):756–777, June 2004.
- [33] D. Nistér and H. Stewénius. A minimal solution to the generalised 3-point pose problem. *Journal of Mathematical Imaging and Vision*, 27(1):67–79, January 2007.
- [34] S. Petitjean. Algebraic geometry and computer vision: Polynomial systems, real and complex roots. *Journal of Mathematical Imaging and Vision*, 10(3):191–220, May 1999.
- [35] N. Snavely, S. M. Seitz, and R. Szeliski. Photo tourism: exploring photo collections in 3D. In *ACM SIGGRAPH'06*, pages 835–846, 2006.
- [36] N. Snavely, S. M. Seitz, and R. Szeliski. Skeletal graphs for efficient structure from motion. In *CVPR'08*, 2008.
- [37] H. Stewénius. *Gröbner Basis Methods for Minimal Problems in Computer Vision*. PhD thesis, Centre for Mathematical Sciences LTH, Lund University, Sweden, 2005.
- [38] H. Stewénius, C. Engels, and D. Nistér. Recent developments on direct relative orientation. *ISPRS Journal of Photogrammetry and Remote Sensing*, 60(4):284–294, 2006.
- [39] H. Stewénius, C. Engels, and D. Nister. An efficient minimal solution for infinitesimal camera motion. In *CVPR'07*, pages 1–8, 2007.
- [40] H. Stewénius, D. Nistér, F. Kahl, and F. Schaffalitzky. A minimal solution for relative pose with unknown focal length. *Image and Vision Computing*, 26(7):871–877, July 2008.
- [41] H. Stewénius, D. Nistér, M. Oskarsson, and K. Åström. Solutions to minimal generalized relative pose problems. In *OMNIVIS'05*, 2005.
- [42] H. Stewénius, F. Schaffalitzky, and D. Nistér. How hard is 3-view triangulation really? In *ICCV'05*, volume 1, pages 686–693, 2005.
- [43] B. Triggs. Camera pose and calibration from 4 or 5 known 3d points. In *ICCV'99*, volume 1, page 278, 1999.

Resumé in Czech

Počítačové vidění vyžaduje schopnost efektivně řešit systémy polynomiálních rovnic. Například určování relativní nebo absolutní polohy kamery, lze formulovat jako minimální problémy, tedy je lze řešit z minimálního počtu vstupních dat. Minimální problémy vedou na systémy polynomiálních rovnic s konečným počtem řešení.

Systémy vycházející z minimálních problémů jsou často komplikované a obecné algoritmy k řešení systémů polynomiálních rovnic pro ně vedou na relativně neefektivní řešení. Proto je pro řešení těchto problémů obvykle zapotřebí navrhnout numericky robustní a výpočetně efektivní specifické algoritmy.

V této disertaci navrhujeme modifikace dvou standardních algebraických technik pro řešení systémů polynomiálních rovnic a to metody založené na Gröbnerových bázích a metody založené na rezultantech, které jsou vhodné právě pro efektivní řešení mnoha problémů v počítačovém vidění a jiných oblastech.

Základní rozdíl mezi prezentovanými specializovanými metodami a standardními obecnými metodami je, že prezentované specializované metody využívají znalosti struktury systému polynomiálních rovnic, který reprezentuje konkrétní problém k návrhu efektivního a stabilního algoritmu na řešení tohoto problému. Při tomto návrhu se část výpočtů společná pro všechny instance daného problému připraví předem, což ušetří čas při opakovaném řešení systémů s identickou strukturou.

Takto vytvořený algoritmus není obecným algoritmem a řeší jen systémy polynomiálních rovnic jednoho tvaru, avšak je rychlejší než obecné algoritmy a proto je vhodný pro aplikace, které se objevují například v počítačovém vidění.

Obě navržené specializované metody mohou být snadno zautomatizovány a takto používány i neodborníky k řešení problémů vedoucích na systémy polynomiálních rovnic. V této disertaci prezentujeme automatický generátor efektivních algoritmů založený na modifikované metodě Gröbnerových bází.

Jako ukázkou užitečnosti obou navržených metod a našeho automatického generátoru v této disertaci prezentujeme nová efektivní a numericky stabilní řešení několika velmi důležitých problémů určování relativní polohy kamer. Většina těchto problémů nebyla v minulosti vyřešena. Mezi těmito problémy jsou problémy určování relativní polohy a kalibračních parametrů kalibrovaných, částečně kalibrovaných (s neznámou ohniskovou vzdáleností) nebo kompletně nekalibrovaných perspektivních kamer či kamer s radiálním zkreslením snímajících obecnou scénu nebo scénu s dominující rovinou.

Všechny tyto algoritmy mohou být efektivně použity v aplikacích jako je lokalizace, rekonstrukce 3D scény či rozpoznávání. Kvalita prezentovaných algoritmů je demonstrována experimenty na syntetických i reálných datech.

Author's Publications

Publications related to the thesis

Impacted journal articles

- [1] Z. Kukelova, M. Bujnak, and T. Pajdla. Polynomial eigenvalue solutions to minimal problems in computer vision. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 34(7):1381–1393, 2012. Authorship: 34-33-33.
- [2] Z. Kukelova and T. Pajdla. A minimal solution to radial distortion autocalibration. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 33(12):2410–2422, December 2011. Authorship: 50-50.
- [3] Z. Kukelova, M. Byröd, K. Josephson, T. Pajdla, and K. Åström. Fast and robust numerical solutions to minimal problems for cameras with radial distortion. *Computer Vision and Image Understanding*, 114(2):234–244, February 2010. Authorship: 30-25-25-10-10.

Publications excerpted by WOS

- [4] M. Bujnak, Z. Kukelova, and T. Pajdla. 3D reconstruction from image collections with a single known focal length. In *IEEE International Conference on Computer Vision (ICCV'09)*, pages 1803–1810, 2009. Authorship: 34-33-33.
- [5] M. Byröd, Z. Kukelova, K. Josephson, T. Pajdla, and K. Åström. Fast and robust numerical solutions to minimal problems for cameras with radial distortion. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR'08)*, Vols 1-12, pages 234–244, 2008. Authorship: 30-25-25-10-10.
- [6] Z. Kukelova, M. Bujnak, and T. Pajdla. Automatic Generator of Minimal Problem Solvers. In *10th European Conference on Computer Vision (ECCV'08)*, volume 5304 of *Lecture Notes in Computer Science*, pages 302–315, 2008. Authorship: 34-33-33.
- [7] Z. Kukelova and T. Pajdla. Two minimal problems for cameras with radial distortion. In *7th Workshop on Omnidirectional Vision, Camera Networks and Non-classical Cameras (OMNIVIS'07)*, 2007. Authorship: 50-50.
- [8] Z. Kukelova and T. Pajdla. A minimal solution to the autocalibration of radial distortion. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR'07)*, 2007. Authorship: 50-50.

Other conference publications

- [9] A. Torii, Z. Kukelova, M. Bujnak, and T. Pajdla. The six point algorithm revisited. In *10th Asian Conference on Computer Vision (ACCV'10 Workshop)*, volume 6469

of *Lecture Notes in Computer Science*, pages 184–193, 2011. Authorship: 25-25-25-25.

- [10] Z. Kukelova, M. Bujnak, and T. Pajdla. Polynomial eigenvalue solutions to the 5-pt and 6-pt relative pose problems. In *British Machine Vision Conference (BMVC'08)*, 2008. Authorship: 34-33-33.
- [11] Z. Kukelova and T. Pajdla. Solving polynomial equations for minimal problems in computer vision. In *Computer Vision Winter Workshop (CVWW'07)*, Graz, Austria, 2007. Authorship: 50-50.

Additional publications

Peer-reviewed journal articles

- [12] M. Bujnak, Z. Kukelova, and T. Pajdla. Efficient solutions to the absolute pose of cameras with unknown focal length and radial distortion by decomposition to planar and non-planar cases. *IPSN Transaction on Computer vision and Application (CVA)*, 4:78–86, May 2012. Authorship: 34-33-33.

Publications excerpted by WOS

- [13] Z. Kukelova, J. Heller and T. Pajdla. Hand-Eye Calibration without Hand Orientation Measurement Using Minimal Solution. In *11th Asian Conference on Computer Vision (ACCV'12)*, 2012. Authorship: 34-33-33.
- [14] M. Bujnak, Z. Kukelova, and T. Pajdla. Making Minimal Solvers Fast. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR'12)*, 2012. Authorship: 34-33-33.
- [15] M. Bujnak, Z. Kukelova, and T. Pajdla. New efficient solution to the absolute pose problem for camera with unknown focal length and radial distortion. In *10th Asian Conference on Computer Vision (ACCV'10)*, volume 6492 of *Lecture Notes in Computer Science*, pages 11–24, 2011. Authorship: 34-33-33.
- [16] Z. Kukelova, M. Bujnak, and T. Pajdla. Closed-form solutions to minimal absolute pose problems with known vertical direction. In *10th Asian Conference on Computer Vision (ACCV'10)*, volume 6493 of *Lecture Notes in Computer Science*, pages 216–229, 2011. Authorship: 34-33-33.
- [17] M. Bujnak, Z. Kukelova, and T. Pajdla. Robust focal length estimation by voting in multi-view scene reconstruction. In *9th Asian Conference on Computer Vision (ACCV'09)*, pages 13–24, 2009. Authorship: 34-33-33.
- [18] M. Bujnak, Z. Kukelova, and T. Pajdla. A general solution to the p4p problem for camera with unknown focal length. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR'08)*, Vols 1-12, pages 3506–3513, 2008. Authorship: 34-33-33.

Citations of Author's Work

- [1] H. Aanaes, K. Josephson, F. Anton, J. A. Baerentzen, and F. Kahl. Camera Re-sectioning from a Box. In *Image Analysis, Proceedings*, volume 5575 of *Lecture Notes in Computer Science*, pages 259–268, 2009. 16th Scandinavian Conference on Image Analysis, Oslo, Norway, Jun 15-18, 2009.
- [2] M. Byröd, K. Josephson, and K. Åström. A Column-Pivoting Based Strategy for Monomial Ordering in Numerical Grobner Basis Calculations. In *10th European Conference on Computer Vision (ECCV'08)*, volume 5305 of *Lecture Notes In Computer Science*, pages 130–143, 2008.
- [3] M. Byröd, K. Josephson, and K. Åström. Fast and Stable Polynomial Equation Solving and Its Application to Computer Vision. *International Journal Of Computer Vision*, 84(3):237–256, Sep 2009.
- [4] Y.-J. Chang and T. Chen. Multi-View 3D Reconstruction for Scenes under the Refractive Plane with Known Vertical Direction. In *IEEE International Conference on Computer Vision (ICCV'11)*, pages 351–358, 2011.
- [5] T. Chaperon, J. Droulez, and G. Thibault. Reliable camera pose and calibration from a small set of point and line correspondences: A probabilistic approach. *Computer Vision And Image Understanding*, 115(5):576–585, May 2011.
- [6] D. Chen, H. Shao, and Q. Dai. Robust Focal Length Estimation Based on Minimal Solution Method. In *3DTV Conference - The True Vision - Capture, Transmission and Display of 3D Video (3DTV-CON'11)*, 2011.
- [7] J. Chen and B. Yuan. Metric 3D Reconstruction from Uncalibrated Unordered Images with Hierarchical Merging. In *IEEE 10TH International Conference on Signal Processing (ICSP'10), Vols I-III*, pages 1169–1172, 2010.
- [8] B. Clipp, C. Zach, J.-M. Frahm, and M. Pollefeys. A New Minimal Solution to the Relative Pose of a Calibrated Stereo Camera with Small Field of View Overlap. In *12th IEEE International Conference on Computer Vision (ICCV'09)*, pages 1725–1732, 2009.
- [9] J. Courchay, A. Dalalyan, R. Keriven, and P. Sturm. Exploiting Loops in the Graph of Trifocal Tensors for Calibrating a Network of Cameras. In *11th European Conference on Computer Vision (ECCV'10)*, volume 6312 of *Lecture Notes in Computer Science*, pages 85–99, 2010.
- [10] J. Courchay, A. S. Dalalyan, R. Keriven, and P. Sturm. On Camera Calibration with Linear Programming and Loop Constraint Linearization. *International Journal Of Computer Vision*, 97(1):71–90, Mar 2012.
- [11] X. Deng, F. Wu, Y. Wu, F. Duan, L. Chang, and H. Wang. Self-calibration of hybrid central catadioptric and perspective cameras. *Computer Vision And Image Understanding*, 116(6):715–729, Jun 2012.

- [12] E. Dunn, B. Clipp, and J.-M. Frahm. A geometric solver for calibrated stereo egomotion. In *IEEE International Conference on Computer Vision (ICCV'11)*, pages 1187–1194, 2011.
- [13] H. Fu and X. Cao. Forgery Authentication in Extreme Wide-Angle Lens Using Distortion Cue and Fake Saliency Map. *IEEE Transactions On Information Forensics And Security*, 7(4):1301–1314, Aug 2012.
- [14] X. Fu and X. Zhang. An Efficient Refinement for Relative Pose Estimation with Unknown Focal Length from Two Views. In *IEEE/ION Position Location And Navigation Symposium (PLANS)*, pages 757–768, 2012.
- [15] R. Hartley and H. Li. An Efficient Hidden Variable Approach to Minimal-Case Camera Motion Estimation. *IEEE Transactions On Pattern Analysis And Machine Intelligence*, 34(12):2303–2314, Dec 2012.
- [16] J. Ho, A. Peter, A. Rangarajan, and M.-H. Yang. An Algebraic Approach to Affine Registration of Point Sets. In *12th IEEE International Conference on Computer Vision (ICCV'09)*, pages 1335–1340, 2009.
- [17] M. Hödlmoser, B. Micusik, and M. Kampel. Camera Auto-Calibration Using Pedestrians and Zebra-Crossings. In *IEEE International Conference on Computer Vision Workshops (ICCV'11 Workshops)*, 2011.
- [18] A. Irschara, Ch. Zach, J-M. Frahm, and H. Bischof. From Structure-from-Motion Point Clouds to Fast Location Recognition. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR'09), Vols 1-4*, pages 2591–2598, 2009.
- [19] H. Jin. A three-point minimal solution for panoramic stitching with lens distortion. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR'08), Vols 1-12*, pages 2681–2688, 2008.
- [20] K. Josephson and M. Byröd. Pose Estimation with Radial Distortion and Unknown Focal Length. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR'09), Vols 1-4*, pages 2411–2418, 2009.
- [21] M. Kalantari, A. Hashemi, F. Jung, and J.-P. Guedon. Relative orientation using 3 points and the vertical direction. A direct approach. *Traitement Du Signal*, 27(3):325–348, 2010.
- [22] J. Kannala, S. Brandt, and J. Heikkila. Self-calibration of central cameras by minimizing angular error. In *3rd International Conference on Computer Vision Theory and Applications, (VISAPP'08), Vol 1*, pages 28-35, 2008.
- [23] M. Kalantari, A. Hashemi, F. Jung, and J.-P. Guedon. A New Solution to the Relative Orientation Problem Using Only 3 Points and the Vertical Direction. *Journal Of Mathematical Imaging And Vision*, 39(3):259–268, Mar 2011.
- [24] L. Kang, L. Wu, and Y.-H. Yang. Experimental study of the influence of refraction on underwater three-dimensional reconstruction using the SVP camera model. *Applied Optics*, 51(31):7591–7603, Nov 1 2012.

- [25] S.-H. Lee, T.-E. Kim, and J.-S. Choi. Correction of Radial Distortion Using a Planar Checkerboard Pattern and Its Image. In *27th IEEE International Conference on Consumer Electronics*, pages 255–256, 2009.
- [26] S.-H. Lee, S.-K. Lee, and J.-S. Choi. Correction of Radial Distortion using a Planar Checkerboard Pattern and its Image. *IEEE Transactions On Consumer Electronics*, 55(1):27–33, Feb 2009.
- [27] H. Li. Multi-View Structure Computation without Explicitly Estimating Motion. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR'10)*, IEEE Conference on Computer Vision and Pattern Recognition, pages 2777–2784, 2010.
- [28] S. Li and Y. Hai. Estimating Camera Pose from H-Pattern of Parking Lot. In *IEEE International Conference on Robotics and Automation (ICRA'10)*, pages 3954–3959, 2010.
- [29] S. Li and Y. Hai. Easy Calibration of a Blind-Spot-Free Fisheye Camera System Using a Scene of a Parking Space. *IEEE Transactions On Intelligent Transportation Systems*, 12(1):232–242, Mar 2011.
- [30] S. Li and C. Xu. A Stable Direct Solution of Perspective-Three-Point Problem. *International Journal Of Pattern Recognition And Artificial Intelligence*, 25(5):627–642, Aug 2011.
- [31] S. Li and C. Xu. Efficient lookup table based camera pose estimation for augmented reality. *Computer Animation And Virtual Worlds*, 22(1):47–58, Jan-Feb 2011.
- [32] S. Li, C. Xu, and M. Xie. A Robust $O(n)$ Solution to the Perspective- n -Point Problem. *IEEE Transactions On Pattern Analysis And Machine Intelligence*, 34(7):1444–1450, Jul 2012.
- [33] J. Lim, N. Barnes, and H. Li. Estimating Relative Camera Motion from the Antipodal-Epipolar Constraint. *IEEE Transactions On Pattern Analysis And Machine Intelligence*, 32(10):1907–U188, Oct 2010.
- [34] L. Liu and I. Stamos. A systematic approach for 2D-image to 3D-range registration in urban environments. *Computer Vision And Image Understanding*, 116(1):25–37, Jan 2012.
- [35] L. Meier, P. Tanskanen, L. Heng, G. H. Lee, F. Fraundorfer, and M. Pollefeys. PIXHAWK: A micro aerial vehicle design for autonomous flight using onboard computer vision. *Autonomous Robots*, 33(1-2):21–39, Aug 2012.
- [36] B. Micusik. Relative pose problem for non-overlapping surveillance cameras with known gravity vector. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR'11)*, 2011.
- [37] B. Micusik and T. Pajdla. Simultaneous surveillance camera calibration and foot-head homology estimation from human detections. In *23rd IEEE Conference on Computer Vision and Pattern Recognition (CVPR), San Francisco, CA, Jun 13-18, 2010*, pages 1562–1569, 2010.

- [38] O. Naroditsky and K. Daniilidis. Optimizing Polynomial Solvers for Minimal Geometry Problems. In *IEEE International Conference on Computer Vision (ICCV'11)*, pages 975–982, 2011.
- [39] O. Naroditsky, X. S. Zhou, J. Gallier, S. I. Roumeliotis, and K. Daniilidis. Two Efficient Solutions for Visual Odometry Using Directional Correspondence. *IEEE Transactions On Pattern Analysis And Machine Intelligence*, 34(4):818–824, Apr 2012.
- [40] G. Paar, L. Waugh, D. P. Barnes, T. Pajdla, M. Woods, H. R. Graf, Y. Gao, K. Willner, J. P. Muller, and R. Li. Integrated Field Testing of Planetary Robotics vision processing - the PRoVisG Campaign in Tenerife 2011. In *Conference on Intelligent Robots and Computer Vision XXIX - Algorithms and Techniques*, volume 8301 of *Proceedings of SPIE*, 2012.
- [41] V. Pradeep and J. Lim. Egomotion using Assorted Features. In *23rd IEEE Conference on Computer Vision and Pattern Recognition (CVPR'10)*, pages 1514–1521, 2010.
- [42] V. Pradeep and J. Lim. Egomotion Estimation Using Assorted Features. *International Journal Of Computer Vision*, 98(2):202–216, Jun 2012.
- [43] S. Ramalingam, S. Bouaziz, P. Sturm, and P. H. S. Torr. The Light-Path Less Traveled. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR'11)*, 2011.
- [44] S. Ramalingam and P. Sturm. Minimal solutions for generic Imaging models. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR'08)*, Vols 1-12, pages 2870–2877, 2008.
- [45] S. Ramalingam, Y. Taguchi, T. K. Marks, and O. Tuzel. P2 Pi: A Minimal Solution for Registration of 3D Points to 3D Planes. In *11th European Conference on Computer Vision (ECCV'10)*, volume 6315 of *Lecture Notes in Computer Science*, pages 436–449, 2010.
- [46] Ch. Strecha, T. Pylvaenäinen, and P. Fua. Dynamic and Scalable Large Scale Image Reconstruction. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR'10)*, pages 406–413, 2010.
- [47] Z. Tang, R. G. von Gioi, P. Monasse, and J.-M. Morel. High-precision camera distortion measurements with a “calibration harp”. *Journal Of The Optical Society Of America A-optics Image Science And Vision*, 29(10):2134–2143, Oct 2012.
- [48] N. Trawny and S. I. Roumeliotis. On the Global Optimum of Planar, Range-based Robot-to-Robot Relative Pose Estimation. In *IEEE International Conference on Robotics and Automation (ICRA'10)*, pages 3200–3206, 2010.
- [49] R. G. von Gioi, P. Monasse, J. M. Morel, and Z. Tang. Towards High-precision Lens Distortion Correction. In *IEEE International Conference on Image Processing (ICIP'10)*, pages 4237–4240, 2010.

- [50] U. von Oehsen, J. M. Marcinczak, A. F. M. Velez, and R.-R. Grigat. Keyframe Selection for Robust Pose Estimation in Laparoscopic Videos. In *Conference on Medical Imaging - Image-Guided Procedures, Robotic Interventions and Modeling*, volume 8316 of *Proceedings of SPIE*, 2012.
- [51] J. Wang, W. Gu, J. Zhu, and J. Zhang. Calibration of Lens Distortion Based on Plane Constraints. In *International Conference on Digital Image Processing (ICDIP'09)*, pages 355–358, 2009. International Conference on Digital Image Processing, Bangkok, Thailand, Mar 07-09, 2009.
- [52] J. Wu and G. Liu. Noniterative calibration of a camera lens with radial distortion. *Measurement Science & Technology*, 23(10), Oct 2012.
- [53] Miao X.-K., Zhu F., and Hao Y.-M. Pose estimation of non-cooperative spacecraft based on collaboration of space-ground and rectangle feature. In *International Symposium on Photoelectronic Detection and Imaging 2011 - Space Exploration Technologies and Applications*, volume 8196 of *Proceedings of SPIE*, 2011.
- [54] S.-J. Zhang, X.-B. Cao, Zhang F., and L. He. Monocular vision-based iterative pose estimation algorithm from corresponding feature points. *Science China-Information Sciences*, 53(8):1682–1696, Aug 2010.