

L1867

Material


Housings made from cold rolled sheet steel with zinc-plated surfaces.

Technical notes

Re-lubricatable. For use with stretcher frame (see our part L1868). For optional shaft end caps add

suffixes:

- CO for two open protective caps (with seal) for through shafts.
- CC for one open and one closed protective caps for shaft ends.

Order No.	d ₁ for h6	l ₁	h ₁	l ₂	h ₂	w ₁	w ₂	w ₃	w ₄	 Kg
L1867.012	12	264	78	225	41	31,0	21	12,7	48,8	1,7
L1867.015	15	264	78	225	41	31,0	21	12,7	48,8	1,7
L1867.017	17	264	78	225	41	31,0	21	12,7	48,8	1,7
L1867.020	20	264	78	225	41	31,0	21	12,7	48,8	1,7
L1867.025	25	264	78	225	41	34,0	21	14,3	48,8	1,7
L1867.030	30	264	78	225	41	38,1	21	15,9	58,4	1,9
L1867.035	35	264	78	225	41	42,9	21	17,5	58,4	2,1
L1867.040	40	274	98	225	41	49,2	21	19,0	75,6	4,2
L1867.045	45	274	98	225	41	49,2	21	19,0	45,6	4,2
L1867.050	50	274	98	225	41	51,6	21	19,0	75,6	4,2

Order No.	d ₂	d ₃	d ₄	Max. dyn. radial load C kN	Max. static radial load C ₀ kN	Max. speed rpm
L1867.012	29,0	R1/8"	60	12,8	6,6	6500
L1867.015	29,0	R1/8"	60	12,8	6,6	6500
L1867.017	29,0	R1/8"	60	12,8	6,6	6500
L1867.020	29,0	R1/8"	60	12,8	6,6	6500
L1867.025	34,0	R1/8"	60	14,0	7,8	6500
L1867.030	40,3	R1/8"	80	19,5	11,2	4500
L1867.035	48,0	R1/8"	80	25,7	15,2	4500
L1867.040	53,0	R1/8"	100	29,6	18,2	3500
L1867.045	57,2	R1/8"	100	31,8	20,8	3500
L1867.050	61,8	R1/8"	100	35,1	23,2	3000